



Finish : Reflector

1	0833	2	0833	3	0000	4		5		6		7		8
SUPERSEDES 9245 003 44500 0833/000 p.190-1 Of 26/08/2011		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 13213Z/98F 2000W 235V REFL					9245 003 44500 0833/000			26/02/2014				
REF. : RDC 2014-001	DOCUMENTATION	UNIT mm	PROJ. EUROP 	2 SH	SH 190-1	10	1:1	A4						
NAME : J.P. CHARLIER	VALIDATION : A. PICHARD			DR. FISCHER Europe										
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.														

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2500 K 2400 K ± 100 K Indicative value
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA
WEIGHT	48 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES : 9245 003 44500 0833/000 p. 190-2 Of 26/08/2011		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 13213F/98F 2000W 235V REFL						9245 003 44500 0833/000			14/01/2013				
REF. :	PDM IRK 2012-060	DOCUMENTATION	UNIT mm	PROJ EUROPE	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															