

QT-ECO 1X26 S

QUICKTRONIC ECONOMIC | ECG for FL 7 mm and CFL



Areas of application

- Public buildings

Product family benefits

- Compact housing
- Automatic restart after lamp replacement
- Large input voltage range

Product family features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50 Hz
- Energy Efficiency Index EEL: A2 / A3 (depending on lamp)
- Automatic shutdown of defective lamps and at end of life (EoL)

Product datasheet

Technical data

Electrical data


Nominal voltage	220...240 V
Mains frequency	50 Hz
Input voltage DC	176...254 V
Operating frequency	35...45 kHz
Max. ECG no. on circuit breaker 10 A (B)	30
Max. ECG no. on circuit breaker 16 A (B)	50
Inrush current	14 A

Light technical data

Starting time	1.5 s ¹⁾
---------------	---------------------

¹⁾ Preheat start: After a switch off, the lamps should remain switched off for 2 minutes to ensure an optimum preheat start

Dimensions & weight



Length	80.0 mm
Width	40.0 mm
Height	22.0 mm
Mounting hole spacing, length	72.0...75.0 mm
Product weight	50.00 g

Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	30000 h ¹⁾
--------------	-----------------------

Product datasheet

¹⁾ $T_c = 70^\circ\text{C}$, with max. 10% failure rate

Additional product data

Suitable for lamp power (1 lamp)	26 W
----------------------------------	------

Capabilities

Suitable for fixtures with prot. class	I / II
End of lamp life safety shutdown	EOL T.2
Max. cable length to lamp/LED module	1.0 m / 0.5 m
Dimmable	No

Certificates & standards


Approval marks – approval	VDE
EEI – Energy Label	A2 BAT ¹⁾
Standards	Acc. to EN 61347-2-3/Acc. to EN 55015:2006 + A1:2007/Acc. to EN 61000-3-2/Acc. to EN 61547
Protection class	III
Type of protection	IP20

¹⁾ For detailed information please see Lamp-ECG combinations

Logistical data











Commodity code	850410809000
----------------	--------------

Wiring Diagram



Wiring diagram

Download Data

File	
	Product Datasheet 321408_ATI QT-ECO 1X26220-240 S (G+GB)
	Certificates 334955_VDE-Marks approval
	Certificates 334983_VDE-Marks approval
	Certificates 335154_Manufacturer's declaration – EN 55015:2006+A1:2007 (300 MHz)
	Certificates 683440_VDE-Marks approvals
	Declarations of conformity 334801_Declaration of conformity
	Operating instructions 592501_EAC QT-ECO
	CAD data 3-dim 313445_80x40x22 9900019
	CAD data 3-dim 313452_80x40x22 9900019
	CAD data 3-dim 313497_80x40x22 9900019

Product datasheet



CAD data PDF
313386_80x40x22 9900019

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321065971	QT-ECO 1X26 S	Shipping carton box 50	212 mm x 142 mm x 170 mm	5.12 dm ³	2791.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

QT-ECO 1X26 S

QUICKTRONIC ECONOMIC | ECG for FL 7 mm and CFL

Product name	Lamp group	Nominal current	Nominal wattage + Power loss	Luminous flux at 25 °C	Number of lighting outlets	EEL – Energy Label
QT-ECO 1X26 S	DULUX D/E 26 W	0.18 A	23.50 W	1600 lm	1	A2 BAT
	DULUX T/E 26 W	0.18 A	23.50 W	1600 lm	1	A2 BAT