



PAR 36 dwe q650par36/1 120v 41667

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent







Product data

EAN Code	0043168416672
DUN Code	00043168416672
Bulb Shape	PAR
Bulb Finish	Aluminized
Bulb Diameter [mm]	114.3
Cap/Base	Screw terminal
Nominal beam angle [°]	21
Gross weight per piece [g]	255
Maximum Overall Length [mm]	70
Net weight per piece [g]	230
Brand	General Electric (GE)

Performance data

Nominal power [W]	650
Nominal lamp voltage [V]	120
Nominal lumens [lm]	1
Nominal correlated colour temperature (CCT) [K]	3200
Rated Life [h]	100
Ballast Required	Yes
Nominal center beam candlepower (CBCP) [cd]	24000
Coil type	CC-6
Energy efficiency class (EEC)	D
Weighted energy consumption [kWh/1000h]	692.4





Logistic data

Pack Quantity	12
Pallet quantity UK (PC)	1200
Outer case size	226 x 211 x 313 (mm)
Layer quantity	1 UK
Layer quantity UK	1
Product status	Available

Application areas



Downloads & Links Go to the catalog site (HTTP)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.